

Pressure transmitter with piezoresistive silicon pressure sensors  
 Explosion flameproof version for Hazardous area  
 with a certification by KOSHA



Since January, 2026



Model: EDN.713  
 Sensor type: Piezo\_resistive silicon sensor  
 Accuracy: ≤ 0.35% F.S  
 Wetted parts: st.steel 316L  
 Application: pressure measurement with LCD & all st. steel housing

Pressure Transmitter	Model	기본판매가격 (원)
----------------------	-------	------------

Model:	EDN.713	1,173,500
--------	---------	-----------

Scope	Code	Specifications	추가사양금액(원)
-------	------	----------------	-----------

Analog output signals	O1	: 4...20mA, 2-wire system	-
	O2	: 0...10V, 3-wire system	-
	O3	: 0...5V, 3-wire system	-
	O4	: 1...5V, 3-wire system	-
	O6	: 0.5...4.5V, 3-wire system	-

Kind of sanitary diaphragm	TR	: Tri-clamp ASME BPE, ISO 1127	-
	GA	: Groove nut, APV-RJT	146,000
	GT	: Groove nut, threaded connection IDF ISO 2853	204,100
	FM	: Flush mounted, hygienic tubes	262,400
	TC	: Tri-Clamp , ASME BPE & ISO 1127 incl. cooling	204,100

Size of sanitary diaphragm	S1	: diaphragm DN20, 3/4"	58,400
	S2	: diaphragm DN25, 1"	-
	S3	: diaphragm DN38, 1 1/2"	-
	S4	: diaphragm DN51, 2"	-
	S5	: diaphragm DN63.5, 2.5"	58,400
	S6	: diaphragm DN76.1, 3"	72,900

Kind of oil filled for calibration	G	: Glycerine	-
	F	: Food & Beverage oil	29,200

Electrical connection	FP	: Flameproof connecting cable gland	-
	M	: M12 plug	20,500

Pressure Ranges / bar	BR19	: -1...0	-
	BR23	: 0...1	
	BR26	: 0...1.6	
	BR28	: 0...2.5	
	BR30	: 0...4	
	BR32	: 0...6	
	BR33	: 0...10	
	BR35	: 0...16	
	BR37	: 0...25	
	BR39	: 0...40	

Pressure transmitter with piezoresistive silicon pressure sensors  
 St. steel body for industrial application  
 with Declaration of conformity, CE



**추가공통 선택사양 [Options]**

Absolute pressure	PAA	: absolute pressure range [5...6 weeks delivery]	100,000
Accuracy upgraded	A7	: ≤ ± 0.25 % F.S	315,000
	A9	: ≤ ± 0.1 % F.S	466,000
	A10	: ≤ ± 0.05 % F.S	621,000
Functions	485	: RS485 digital communication	102,100
	2SW	: 2 relay switches	102,100
Operating temperature	T4	: -40...+125 °C	61,300
4-wires system for current	C4	: 4...20mA, 4-wire system (+Vcc, +signal, -Vcc, -signal)	11,300
Postprocess	AC50	: Corrosion-protective covering with Teflon to wetted parts	13,300
	AC51	: O-ring ETFE, FKM80 for sealing with sensor	3,100
Accessories	AC20	: Washer, aluminium a/w G1/4"A & G1/2"A-EN 837	2,100
	AC23	: Metal gasket(Sealing gasket), 316L for hole 12.4mm	5,700
	AC24	: Metal gasket(Sealing gasket), brass for hole 12.4mm	4,000
	AC25	: Restrictor screw [oripis] made of st. steel	1,900
	AC40	: Cooling device upto 200 °C	306,200
	AC41	: Cooling device upto 300 °C	400,000
	TP	: St steel tag plate, 60 x 20 x 0.5t	9,500
	GK4	: Gasket, aluminium for thread G1/4"	3,000
Flying cable / IP67	ACM	: 2m flying cable + additional extension cable /m	2,100
Certificates	DMCC	: DAHO manufacturing calibration card	price included
	KC	: KOLAS calibration certificate	KOLAS 교정비용 참조

**KOLAS 국제인증 교정수수료**

	압력변환기 / 전송기		12	표준, 종합 교정절차시 실비	기본교정료	표준소급료	VAT별도
20412	1	압력변환기-절대압용 압력계			171,500	17,150	188,650
	2	압력변환기-게이지압용 압력계			114,700	11,470	126,170
	3	압력변환기-차압용 압력계			118,200	11,820	130,020
	4	압력변환기-기압계용 압력계			114,700	11,470	126,170
	5	압력변환기-고압용 압력계 (100MPa 이상인 계기)		100 MPa 이상인 계기	143,600	14,360	157,960
	6	압력변환기-미압용 압력계 (0.01 MPa 이하인 계기)		0.01 MPa 이하인 계기	124,100	12,410	136,510
	7	압력변환기-동압용 압력계		실비			

※ 다호 제품 또는 수입공급하는 제품을 구매할 경우에 "KOLAS 국제공인 교정료"에서 50% 할인 적용하며, 연간계약 또는 특별고정할인 그리고 구매수량에 따른 할인 적용업체는 중복할인적용이 되지 않습니다.

Product code	Photos	Specifications
AC20		Model : Washer, aluminium for pressure connection EN837 Applied for : Sealing for G1/4" & G1/2" Thickness : 4 mm Outer diameter : 14.5 mm
AC23		Product name: : Metal gasket for hole 12.4mm Material : st. steel 316L Application: : Sealing washer for high temperature Hole diameter : Outer :
AC24		Product name: : Metal gasket for hole 12.4mm Material : Brass Application: : Sealing washer for high temperature Hole diameter : Outer :
AC25		Product name: : Restrictor screw [oripis] Material : stainless steel Application: : against pulsation Hole diameter : 0.15mm Outer : less 3mm
AC40		Model : Cooling device Application : Temperature upto 200°C only for pressure transmitters Material : SUS 316 No. of fins : 5 Pressure conn. : G1/4", G1/2"
AC41		Model : Cooling device Application : Temperature upto 300°C a/w diaphragm seals Material : SUS 316 No. of fins : 5 Pressure conn. : G1/4", G1/2"
AC45		Model : Square Indicator, LCD Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43650A made of plastic
AC46		Model : Square Indicator, LED Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43650A, plastic made of plastic