

Piezoresistive silicon digital pressure gauge
Digital manometer
MAX.- and min.- function / accuracy 0.1%F.S

DAHO

2024.05.13.



Model	LEO-2 / LEO-2 Ei
Sensor type	Piezoresistive silicon sensor
Accuracy	Accuracy < 0.1% FS
Wetted part	St. Steel 316L (DIN 1.4435)
Application	air, oil, water as well as aggressive media

(Currency : KRW)

Specification	Code	List Price
---------------	------	------------

		<i>[QPDR: Group "A"]</i>	<i>Standard Price</i>
Model	LEO 2		
Analog output signals	O0 : None		-
Electrical connection	E0 : LCD Display		-
Pressure Connection	G4 : G1/4" (adapter with swivel)		-
Pressure Range	R30 : 0...4 bar (abs.) [in stock]		867,000
	R67 : 0...11 bar (abs.) [in stock]		867,000
	R68 : 0...31 bar (abs.) [in stock]		867,000
	R71 : 0...101 bar (abs.) [in stock]		867,000
	R49 : 0...300 bar [in stock]		867,000
	R53 : 0...700 bar [in stock]		975,000

		<i>[QPDR: Group "C"]</i>	<i>Standard Price</i>
Intrinsical safe version	LEO-2 Ei, Ex-version		
Analog output signals	O0 : None		-
Electrical connection	E0 : LCD Display		-
Pressure Connection	G4 : G1/4" (adapter with swivel)		-
Pressure Range	R10 : -1...3 bar [non stock item]		1,067,600
	R02 : -1...30 bar [non stock item]		1,067,600
	R49 : 0...300 bar [non stock item]		1,067,600
	R53 : 0...700 bar [non stock item]		1,168,600

Options

Accessories	CD2 : Cooling device up to 200 °C	250,000
	CD3 : Cooling device up to 300 °C	300,000
	A42 : G1/4(F) x G1/2(M)	175,000
	A4M : G1/4(F) x M20x1.5(M)	175,000
	RP : Rubber protection	57,900
	CS : Soft carrying case	81,900
	BT : Battery (CR2430, 3V, 285mAh)	81,900
	FS : adapter with swivel (7/16"-20UNF female to 1/4" male)	144,600

Certificates

Certificates	CC : Calibration Certification by Keller (with 5 measuring points)	202,200
	DMCC : DAHO manufacturing calibration card	8,000
	KC : KOLAS calibration certificate	Refer to KOLAS List Price