

Piezoresistive silicon differential pressure transmitter
 Housing & wetted parts are made of all st. steel for industrial application
 with Declaration of conformity, CE

DAHO

Since January, 2026



Model: EDN.750
 Sensor type: Piezo_resistive silicon sensor
 Accuracy: $\leq 0.5\% \text{ FS} / 0.25\% / 0.1\% \text{ F.S}$
 Wetted parts: st. steel 316L
 Application: air, oil, water as well as aggressive media

Pressure Transmitter	Model	기본 판매가격(원)
Model: EDN.750	A4 : accuracy $\leq 0.5\%$	883,700
	A7 : accuracy $\leq 0.25\%$	1,104,700
	A9 : accuracy $\leq 0.1\%$	1,472,900

Scope	Code	Specifications	선택 사양 추가금액(원)
Analog output signals	O1	: 4...20mA, 2-wire system	-
	O2	: 0...10V, 3-wire system	
	O3	: 0...5V, 3-wire system	
	O4	: 1...5V, 3-wire system	
	O5	: 0.5...4.5V / 5V, ratio-metric	
	O6	: 0.5...4.5V, 3-wire system	
Electrical connection	FP	: Flameproof connecting cable gland	-
	M	: M12 plug	20,500
RS485 function	RS	: RS485 digital communication	102,100
2 switches	SW	: 2 switches, SW1 & SW2	102,100
Pressure connection	G4	: female G 1/4" + female G 1/4"	-
	R4	:	
	N4	: female NPT 1/4" + female NPT 1/4"	
	XX	: Others	
Pressure Ranges / bar	R126	0...25 mbar	no additional costs
	R128	0...40 mabr	
	R130	0...60 mbar	
	R131	0...100 mabr	
	R133	0...160 mbar	
	R135	0...250 mabr	
	R137	: 0...400 mbar	
	R21	: 0...600 mbar	
	R23	: 0...1 bar	
	R26	: 0...1.6 bar	
	R28	: 0...2.5 bar	
	R30	: 0...4 bar	
	R32	: 0...6 bar	
	R33	: 0...10 bar	
	R35	: 0...16 bar	
	R37	: 0...25 bar	
	R38	: 0...35 bar	

Options

1. Accessories	TP	: St steel tag plate, 60 x 20 x 0.5t	9,500
	adapter	: male G1/4" + male G1/4", 2 pcs	81,750
2. Cable length	2MH	: 2m Standard, additional 1m	2,000
3. Certificates	DMCC	: DAHO manufacturing calibration card	included
	KC	: KOLAS calibration certificate	refer to KOLAS list price



Piezoresistive silicon differential pressure transmitter
 Housing & wetted parts are made of all st. steel for industrial application
 with Declaration of conformity, CE



A. Options

Specifications	Descriptions	Unit price(₩)
Operating temperature	T4 : -40...+125 °C	63,200
4-wires system for current	C4 : 4...20mA, 4-wire system (+Vcc, +signal, -Vcc, -signal)	11,600
Postprocess	AC50 : Corrosion-protective covering with Teflon to wetted parts	13,900
	AC51 : O-ring PTFE, FKM80 for sealing with sensor	3,100
Accessories	AC45 : LCD Square Indicator, only for 4...20mA output	158,000
	AC46 : LED Square Indicator, only for 4...20mA output	158,000
	TP : St steel tag plate, 60 x 20 x 0.5t	10,000
	GK4 : Gasket, aluminium for thread G1/4"	3,100
Flying cable / IP67	ACM : 2m flying cable + additional extension cable /m	2,200
Certificates	DMCC : DAHO manufacturing calibration card	price included
	KC : KOLAS calibration certificate	KOLAS 교정비용 참조

B. Specification of accessories

Product code	Photos	Specifications
AC45		Model : Square Indicator, LCD Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43750A made of plastic
AC46		Model : Square Indicator, LED Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43750A, plastic made of plastic

C. KOLAS 국제공인 교정성적서 수수료

분류 번호	측정기명	교정 주기	교정료			
			표준, 종합 교정절차시 실비	기본교정료	표준소급료	VAT별도
20412	압력변환기 / 전송기	12				
	1 압력변환기-절대압용 압력계			171,500	17,150	188,650
	2 압력변환기-게이지압용 압력계			114,700	11,470	126,170
	3 압력변환기-차압용 압력계			118,200	11,820	130,020
	4 압력변환기-기압계용 압력계			114,700	11,470	126,170
	5 압력변환기-고압용 압력계 (100MPa 이상인 계기)		100 MPa 이상인 계기	143,600	14,360	157,960
	6 압력변환기-미압용 압력계 (0.01 MPa 이하인 계기)		0.01 MPa 이하인 계기	124,100	12,410	136,510
	7 압력변환기-동압용 압력계		실비			

※ 다호 제작품 또는 수입공급하는 제품을 구매할 경우에 "KOLAS 국제공인 교정료" 에서 50% 할인 적용하며,
 연간계약 또는 특별교정할인 그리고 구매수량에 따른 할인 적용업체는 중복할인적용이 되지 않습니다.