

**Pressure gauge with chemical seals**  
**Diaphragm type pressure gauge seires MDH**  
**Glycerin / silicon liquid filled**



Model	MDH
Element type	Diaphragm
Accuracy	refer to pressure gauge
Wetted parts:	Stainless steel 316
Application:	Food, pharmaceutical, biotechnology industries

Specification	Code	Currency (원)
<b>Standard Price</b>	MDH	130,000
<b>Additional Prices</b>		
Pressure gauge	B3 : MBX3, 0...100 bar to 0...400 bar	-
	B5 : MBX5, 0...100 bar to 0...400 bar	40,600
	A3 : MAX3, 0...100 bar to 0...400 bar	8,200
	A4 : MAX4, 0...100 bar to 0...400 bar	31,200
	A5 : MAX5, 0...100 bar to 0...400 bar	54,200
Type of mounting	1 : Bottom connection	-
Liquid filling	0 : Dry	-
	1 : Glycerin	7,600
	2 : Silicon	30,100
Pressure connection	G4 : G1/4"(PF1/4")	-
	R4 : R1/4"(PT1/4")	-
	G1 : G3/4"(PF3/4")	15,100
	G0 : G1"(PF1")	30,100
	XX : Others	on request
Unit of measurement	B : bar	-
	K : kPa	-
	M : MPa	-
	P : psi	-
	D : dual scale (MPa-inner & bar-outer)	-
	X : others	on request
Pressure Ranges / bar	R43 : 0...100	no extra charges
	R45 : 0...160	
	R47 : 0...250	
	R50 : 0...400	

**Options**

1. Filling liquid	FG : Glycerin	15,100
	FV : Vegetable oil	30,100
	FH : High Temperature oil	30,100
2. Diaphragm	TC : Diaphragm teflon coating	97,800
3. On dial face	OR : Other pressure range per pcs	15,100
	ND : New dial face design	120,300
	NF : New dial face printing cost per pcs	4,600
	GM : Green marking per pcs	4,600
	CD : New dial face design with company logo	75,200
4. Certificates	DMCC : Manufacture standard calibration report	8,500
	KC : KOLAS calibration certificate	refer to KOLAS list price