



Model	EDN.338
Sensor type:	piezoresistive silicon pressure sensors
Accuracy:	≤ ± 0.5%
Wetted parts:	all stainless steel
Application:	for heat exchanger

Pressure Transmitter	Model	기본판매가격(원)
----------------------	-------	-----------

Model:	EDN.338	128,900
<i>min. order q'ty ≥ 20 pcs per order & possible, mixed pressure ranges</i>		

Scope	Code	Specifications	선택사항 추가금액(원)
-------	------	----------------	--------------

Analog output signals	O1	: 4...20mA, 2-wire system	-
	O2	: 0...10V, 3-wire system	-
	O3	: 0...5V, 3-wire system	-
	O4	: 1...5V, 3-wire system	-
	O6	: 0.5...4.5V, 3-wire system	-
	Electrical connection	D	: DIN 43650 A
P		: mPm plug	-
M		: M12 plug	21,000
C		: 2m flying cable	10,300
Pressure connection	R4	: R 1/4" (PT 1/4")	-
	R3	: R 3/8" (PT 3/8")	-
	R2	: R 1/2" (PT 1/2")	-
	G4	: G 1/4" (PF 1/4")	-
	G3	: G 3/8" (PF 3/8")	-
	G2	: G 1/2" (PF 1/2")	-
	XX	: Others	<i>문의 & 추가금액발생</i>
Pressure Ranges / bar	R01	: -1...+ 50 bar	-
	R02	: -1...+ 35 bar	-
	R05	: -1...+ 24 bar	-
	R06	: -1...+ 20 bar	-
	R07	: -1...+ 15 bar	-
	R09	: -1...+ 9 bar	-
	R11	: -1...+ 5 bar	-
	R19	: -1...0 bar	-
	R33	: 0...10 bar	-
	R35	: 0...16 bar	-
	R37	: 0...25 bar	-
R39	: 0...40 bar	-	

※ Other pressure ranges are on request.

Piezoresistive silicon pressure transmitter
 St. steel body for industrial application
 with Declaration of conformity, CE



추가선택사양

Absolute pressure	PAA	: absolute pressure range [5...6 weeks delivery]	105,300
	AU	: Gold plated piezoresistive pressure sensor	335,800
Operating temperature 4-wires system for current	T4	: -40...+125 °C	63,200
	C4	: 4...20mA, 4-wire system (+Vcc, +signal, -Vcc, -signal)	11,600
Postprocess	AC50	: Corrosion-protective covering with Teflon to wetted parts	14,000
	AC51	: O-ring PTFE, FKM80 for sealing with sensor	3,300
Accessories	AC20	: Washer, aluminium a/w G1/4"A & G1/2"A-EN 837	2,200
	AC25	: Restirctor screw [oripis] made of st. steel	2,000
	AC40	: Cooling device upto 200 °C	306,200
	AC41	: Cooling device upto 300 °C	400,000
	AC45	: LCD Square Indicator, only for 4...20mA output	158,000
	AC46	: LED Square Indicator, only for 4...20mA output	158,000
	TP	: St steel tag plate, 60 x 20 x 0.5t	10,000
	GK4	: Gasket, aluminium for thread G1/4"	3,100
	NO	: Washing for application like "USE NO OIL" per pcs	10,800
Flying cable / IP67	ACM	: 2m flying cable + additional extension cable /m	2,200
Underwater plug / IP68	5MCW	: 5m underwater cable standard length	171,900
	ACMW	: additional extension underwater cable /m	6,500
Company Logo	CD	: The first printing of LOGO by Laser on each model - only English or/and Korean characters, not graphic	107,500
Certificates	DMCC	: DAHO manufacturing calibration card	price included
	KC	: KOLAS calibration certificate	KOLAS 교정비용 참조

KOLAS 국제인증 교정수수료

압력변환기 / 전송기		12	표준, 종합 교정절차시 실비	기본교정료	표준소급료	VAT별도	
20412	1	압력변환기-절대압용 압력계		171,500	17,150	188,650	
	2	압력변환기-게이지압용 압력계		114,700	11,470	126,170	
	3	압력변환기-차압용 압력계		118,200	11,820	130,020	
	4	압력변환기-기압계용 압력계		114,700	11,470	126,170	
	5	압력변환기-고압용 압력계 (100MPa 이상인 계기)		100 MPa 이상인 계기	143,600	14,360	157,960
	6	압력변환기-미압용 압력계 (0.01 MPa 이하인 계기)		0.01 MPa 이하인 계기	124,100	12,410	136,510
	7	압력변환기-동압용 압력계		실비			

※ 다호 제작품 또는 수입공급하는 제품을 구매할 경우에 "KOLAS 국제공인 교정료"에서 추가 50% 할인 적용하며, 연간계약 또는 특별고정할인 그리고 구매수량에 따른 할인 적용업체는 중복할인적용이 되지 않습니다.

Piezoresistive silicon pressure transmitter
St. steel body for industrial application
with Declaration of conformity, CE



Product code	Photos	Specifications
AC20		Model : Washer, aluminium Applied for : Sealing for G1/4" & G1/2" Thickness : 4 mm Outer diameter : 14.5 mm
AC25		Product name: : Restrictor screw [oripis] Material : stainless steel Application: : against pulsation Hole diameter : 0.15mm Outer : less 3mm
AC40		Model : Cooling device upto 200°C Application : cooling down temperature 200 °C only for pressure transmitters Material : SUS 316 No. of fins : 5 Pressure conn. : G1/4", G1/2"
AC41		Model : Cooling device Application : Temperature upto 300°C a/w diaphragm seals Material : SUS 316 No. of fins : 5 Pressure conn. : G1/4", G1/2"
AC45		Model : Square Indicator, LCD Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43650A made of plastic
AC46		Model : Square Indicator, LED Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43650A, plastic made of plastic