

Ordering information

MODEL CODE

MAX

Dial size

1 : 40 mm	5 : 100 mm
2 : 50 mm	6 : 125 mm
3 : 63 mm	7 : 150 mm
4 : 80 mm	8 : 160 mm

Mounting

- 1 : Bottom connection (type A)
- 2 : Bottom connection with back flange (type B)
- 3 : Back connection (type D)
- 4 : Back connection with front flange (type BD)

Liquid filling

- 0 : Dry
- 1 : Glycerin
- 2 : Silicon

Option

Refer to option table

Pressure range

Refer to pressure range table

Unit of measurement

B : bar D : dual scale
M : MPa (MPa / bar)
P : psi X : others

Process connection

G2 : PF 1/2" N2 : NPT 1/2"
G3 : PF 3/8" N3 : NPT 3/8"
G4 : PF 1/4" N4 : NPT 1/4"
R2 : PT 1/2" U1 : UNF 7/16"-20 male
R3 : PT 3/8" U2 : UNF 7/16"-20 female
R4 : PT 1/4" H1 : UNF 5/8"-18 female
 H2 : M16 x 1.5 female

Pressure range code, unit bar

Code	Range	Code	Range	Code	Range	Code	Range
R01	-1...50	R16	-1...1	R31	0...5	R46	0...200
R02	-1...35	R17	-1...0.6	R32	0...6	R47	0...250
R03	-1...30	R18	-1...0.25	R33	0...10	R48	0...300
R04	-1...25	R19	-1...0	R34	0...15	R49	0...350
R05	-1...24	R20	-0.6...0	R35	0...16	R50	0...400
R06	-1...20	R21	0...0.6	R36	0...20	R51	0...450
R07	-1...15	R22	0...0.8	R37	0...25	R52	0...500
R08	-1...10	R23	0...1	R38	0...35	R53	0...600
R09	-1...9	R24	0...1.2	R39	0...40	R54	0...700
R10	-1...6	R25	0...1.5	R40	0...50	R55	0...1000
R11	-1...5	R26	0...1.6	R41	0...60	R56	0...1600
R12	-1...4	R27	0...2	R42	0...70	R57	0...2000
R13	-1...3	R28	0...2.5	R43	0...100	R58	0...2500
R14	-1...2	R29	0...3	R44	0...150	RYY	Others
R15	-1...1.5	R30	0...4	R45	0...160		

Option code

Code	Description	Code	Description
ND	New dial design	TP	St. stell tag plate, 60 x 20 x 0.5t
NF	New dial face printing cost per pcs	MC	Manufacture calibration certificate
GM	Green marking per pcs	KC	KOLAS Ilac-MRA calibration certificate
CD	New dial face design with company logo	R	Reed switch
RS	Restrictor screw in socket hole for high pulsation	SN	Snubber
UC	U-calmp for back connection, steel	AD	Adaptor
NO	"USE No OIL" per pcs, at least ≥ 10 pcs	CC	Certificate of conformance / orign
OF	Oval 3-hole front flange	PM	2" Pipe mounting bracket
MP	Maximum pointer	NC	Ni-Cr Plate
BB	Bayonet bezel ring for MBX5	AL	Aluminium pointer for MBX3

How to order

MBXK.510.G2DR40.GM

MBXK, 100mm, A-type, Dry, PF 1/2", 0...25 bar/MPa, Green marking(custom)