



Model	CHS
Element type	Diaphragm
Accuracy	refer to pressure gauge
Wetted parts:	St. steel
Application:	Food, pharmaceutical, biotechnology industries

Specification	Code	Currency (원)
Standard Price	CHS without block flange	451,200
Additional Prices		
Pressure gauge	3 : MAX3, 0...40 bar to 0...600 bar	64,400
	4 : MAX4, 0...40 bar to 0...600 bar	79,300
	5 : MAX5, 0...40 bar to 0...600 bar	94,100
Type of mounting	1 : Bottom connection	-
Liquid filling	0 : Dry	-
	1 : Glycerin	15,100
Pressure connection	B1 : Block flange	55,500
	B2 : without block flange	-
Unit of measurement	B : bar	-
	K : kPa	-
	M : MPa	-
	P : psi	-
	D : dual scale (MPa-inner & bar-outer)	-
	X : others	on request
Pressure Ranges / bar	R39 : 0...40	5,500
	R41 : 0...60	
	R43 : 0...100	no extra charges
	R45 : 0...160	
	R47 : 0...250	
	R50 : 0...400	55,500
	R53 : 0...600	
	R55 : 0...1000	on request

Options

1. On dial face	OR : Other pressure range per pcs	15,100
	ND : New dial face design	75,200
	NF : New dial face printing cost per pcs	4,600
	GM : Green marking per pcs	4,600
	CD : New dial face design with company logo	120,400
2. Accessories	RS : Restrictor screw in socket hole for high pulsation	2,300
	UC : U-clamp for back connection, steel	15,100
	NO : Washing for application "USE NO OIL" per pcs, at least ≥ 10 pcs	3,800
	SG : Safety glass	3,100
	FF : Front flange with 3-hole, stainless steel	3,800
	BF : Back flange with 3-hole, stainless steel	3,800
	TP : St steel tag plate, 60 x 20 x 0.5t	9,500
3. Certificates	DMCC : Manufacture calibration certificate	8,500
	KC : KOLAS / ilac-MRA calibration certificate	refer to KOLAS list price