



Model	ODi-5H
Sensor type	Piezoresistive silicon sensor
Accuracy	Accuracy 0.2% FS
Wetted part	304SS
Application	Gas or liquid

(Currency : KRW)

Specification	Code	List Price
		<i>Standard Price</i>
Model:	ODi-5H : 100 mm	313,000
		<i>[QPDR: Group "A"] Additional Prices</i>
Pressure Connection	G2 : PF 1/2"	-
	N2 : NPT 1/2"	on request
Pressure Range / bar	R21 : -1...0	
	R14 : -50...50 mbar	25,000
	R07 : -1...10 bar	
	R29 : 0...1	
	R97 : 0...60 mbar	
	R23 : 0...100 mbar	
	R25 : 0...250 mbar	
	R32 : 0...2.5	
	R34 : 0...4	
	R36 : 0...6	
	R37 : 0...10 / stock	
	R38 : 0...16	No extra costs
	R40 : 0...25 / stock	
	R42 : 0...40	
	R44 : 0...60	
	R45 : 0...100	
	R46 : 0...160	
	R48 : 0...250 / stock	
	R50 : 0...400	
	R52 : 0...600 / stock	
	R54 : 0...1000	95,000

**Option**

Accessories	CD2 : Cooling device up to 200 °C	200,000
	CD3 : Cooling device up to 300 °C	229,000
	A42 : G1/4(F) x G1/2(M)	175,000
	A4M : G1/4(F) x M20x1.5(M)	175,000
Certificates	MC : DAHO function test report	8,000
	KC : KOLAS calibration certificate	Refer to KOLAS List Price

