

Piezoresistive silicon pressure transmitter
 St. steel body for industrial application
 with Declaration of conformity, CE

DAHO
 2024.02.05



Model	EDN.303
Sensor type	Piezo_resistive silicon sensor
Accuracy	≤ 0.3%
Wetted parts:	st. steel 316L
Application:	air, oil, water as well as aggesive media

Pressure Transmitter	Model	기본 판매가격(원)
----------------------	-------	------------

Model:	EDN.303	327,000
--------	---------	---------

Scope	Code	Specifications	선택사양 추가금액(원)
-------	------	----------------	--------------

Analog output signals	O1	4...20mA, 2-wire system	-
	O2	0...10V, 3-wire system	-
	O3	0...5V, 3-wire system	-
	O4	1...5V, 3-wire system	-

Electrical connection	D	DIN 43650 A	-
	M	M12 plug	20,500
	C	2m Cable	5,000

Pressure connection	G2	G 1/2" (PF 1/2")	-
	G3	G 3/8" (PF 3/8")	-
	G4	G 1/4" (PF 1/4")	-
	R2	R 1/2" (BSPT 1/2")	-
	R3	R 3/8" (BSPT 3/8")	-
	R4	R 1/4" (BSPT 1/4")	-
	XX	Others	추가금액 발생

Pressure Ranges / bar	R19	-1...0	
	R23	0...1	
	R26	0...1.6	
	R28	0...2.5	
	R30	0...4	
	R32	0...6	
	R33	0...10	
	R35	0...16	
	R37	0...25	
	R39	0...40	
	R41	0...60	
	R43	0...100	
	R45	0...160	
	R47	0...250	
	R50	0...400	
R53	0...600		
R55	0...1000		

[선택사양]

Operating temperature	T4	-40...+125 °C	60,000
-----------------------	----	---------------	--------

Accessories	CD2	Cooling device up to 200 °C	250,000
	CD3	Cooling device up to 300 °C	300,000
	TP	St steel tag plate, 60 x 20 x 0.5t	9,500

Cable length	2MC	2m cable standard	5,000
	ACM	additional extension cable /m	2,000

Certificates	DMCC	DAHO manufacturing calibration card	price included
	KC	KOLAS calibration certificate	KOLAS 교정비용 참조하세요