

Piezoresistive silicon level transmitter
High precise level transmitter
for Hazardous Applications

DAHO

2024.01.01



Model	36XW Ei
Sensor type	Piezoresistive silicon sensor
Accuracy	Accuracy ± 0.04% FS
Wetted part	Stainless Steel 316L (DIN 1.4435) / Viton® / PE
Application	cold water for level measurement

(Currency : KRW)

Specification	Code	List Price
Sensor Version	PR : Vent gauge, Zero at atmospheric pressure	-
	PAA : Absolute. Zero at vacuum	-
Model	36XW Ei High precise level transmitter	
	[QPDR: Group "C"]	Standard Price
Analog output signals	O1 : 4...20mA, 2-wire system and RS485	-
	O2 : 0...10V, 3-wire system and RS485	-
	O7 : 0.1...2.5V / 3.2...32V, 3-wire system and RS485	-
Electrical connection	C : 2m Cable	-
Pressure Range	R24 : 0...0.3 bar (3 mH2O)	on request
	R29 : 0...1 bar (10 mH2O)	2,555,200
	R33 : 0...3 bar (30 mH2O)	
	R37 : 0...10 bar (100 mH2O)	2,555,200
	R41 : 0...30 bar (300 mH2O)	
	RYY : Others	Plus 50%
Option		
Accessories	K114B Converter	851,800
	K107 : Converter	1,087,500
Cable Length	Additional Cable length per 1m	가격문의시 견적제출
Tag. Name plate	TAG : Tag. Name plate, made of st. steel (60 x 20 x 0.5t)	20,000
Temperature Range	OTP : Other temperature range, -20...85°C (optional)	952,800
Certificates	CC : Calibration Certification by Keller (with 5 measuring points)	202,200
	DMCC : DAHO manufacturing calibration card	not available
	KC : KOLAS calibration certificate	not available