



Model	ODi-3G
Sensor type	Piezoresistive ceramic sensor
Accuracy	Accuracy 1.0% FS
Wetted part	304SS
Application	Gas or liquid

(Currency : KRW)

Specification	Code	List Price
		<i>Standard Price</i>
Model:	ODi-3G : 65 mm	105,300
		<i>[QPDR: Group "A"] Additional Prices</i>
Pressure Connection	G4 : PF 1/4"	-
	N4 : NPT 1/4"	on request
Pressure Range / bar	R19 : -1...0	16,000
	R26 : 0...1.6	
	R28 : 0...2.5	
	R30 : 0...4	
	R32 : 0...6	
	R33 : 0...10 / stock	
	R35 : 0...16 / stock	
	R37 : 0...25	
	R39 : 0...40 / stock	
	R41 : 0...60	
	R43 : 0...100 / stock	
	R45 : 0...160	
	R47 : 0...250 / stock	
	R50 : 0...400	
	R53 : 0...600	72,700
R54 : 0...700		

No extra costs

Option

Accessories	AC40 : Cooling device up to 200 °C	306,200
	AC41 : Cooling device up to 300 °C	400,000
	PCA : Adapter, female G1/4" x male R1/4",R3/8",R1/2",G3/8",G1/2"	21,600
Certificates	DMCC : DAHO manufacturing calibration card	<i>Price included</i>
	KC : KOLAS calibration certificate	Refer to KOLAS List Price

