

Piezoresistive silicon digital pressure gauge
 Digital manometer, LEO-2 & LEO-2 Ei
 MAX.- and min.- function / accuracy 0.1%F.S



Since January, 2026



Model	LEO-2 & LEO-2 Ei
Sensor type	Piezoresistive silicon sensor
Accuracy	Accuracy < 0.1% FS
Electrical connection	LCD Display
Wetted part	St. Steel 316L (DIN 1.4435)
Pressure Connection	G1/4" with swivel adapter
Application	air, oil, water as well as aggressive media



Model: **LEO-2** [재고보유판매품] List price [원]

Pressure Range	R30 : 0...4 bar (abs.)	1,291,700
	R67 : 0...11 bar (abs.)	1,291,700
	R68 : 0...31 bar (abs.)	1,291,700
	R71 : 0...101 bar (abs.)	1,291,700
	R49 : 0...300 bar	1,291,700
	R53 : 0...700 bar	1,381,700

Model: **LEO-2 Ei** [Intrinsically safe] [비재고품] List price [원]

Pressure Range	R30 : 0...4 bar (abs.)	별도견적요구
	R67 : 0...11 bar (abs.)	별도견적요구
	R68 : 0...31 bar (abs.)	별도견적요구
	R71 : 0...101 bar (abs.)	별도견적요구
	R49 : 0...300 bar	별도견적요구
	R53 : 0...700 bar	별도견적요구

Options

Accessories	PCA : Adapter, female G1/4" x male R1/4",R3/8",R1/2",G3/8",G1/2"	21,600
	RP : Rubber protection	142,500
	CS : Soft carrying case	106,900
	BT : Battery (CR2430, 3V, 285mAh)	15,700
	FS : Swivel incl. fitting (7/16-20 UNF to G1/4)	178,100
	SW : Swivel only	71,300
Certificates	CC : Calibration Certification by Keller (with 5 measuring points)	320,500
	DMCC : DAHO manufacturing calibration card	8,500
	KC : KOLAS calibration certificate	Refer to KOLAS test certificates

KOLAS 국제인증 교정수수료

	측정기명	12	표준, 종합 교정절차시설투비	기본 교정료	표준 소급료	VAT 별도
20406	절대압계, 다이얼, 디지털					
	1 절대압계, 다이얼, 디지털					
	2 디지털 압력계 - 절대압용 압력계			209,800	20,980	230,780
	2 기압계, 수은, 아네로이드, 디지털, 기압기록계 등					
	3 디지털 압력계 - 기압계용 압력계			85,700	8,570	94,270
20408	연성압력계					
	2 디지털 압력계-연성압력계			94,800	9,480	104,280
20409	차압계, 디지털, 다이얼 포함					
	2 디지털 압력계 - 차압용 압력계			85,700	8,570	94,270
20411	게이지압용 압력계; 다이얼, 디지털 등					
	1 2 디지털 압력계 - 게이지압용 압력계			85,700	8,570	94,270
	고압용 압력계: 100 Mpa 이상		실비			
	2 2 디지털 압력계 - 고압용 압력계			267,900	26,790	294,690

※ 다호 제작품 또는 취급 제품을 구매할 경우에 교정료 50% 할인 적용하며, 정규 교정할인 업체는 중복할인 적용이 불가합니다.