

Bellows differential pressure gauge
Diff. pressure gauge series DPA5
Base Pressure 5MPa (50 bar)



Since January, 2026



Model	DPA5
Element type	Bellows
Accuracy	± 1.5 of Full Scale
Wetted parts:	St. steel
Application:	Low and high pressure of air and liquid

Specification	Code	Currency (원)
Standard Price	DPA5 / 100 mm	2,070,700
Additional Prices		
Type of mounting	P : 2" pipe mounting bracket	-
Pressure connection	R4 : R1/4" (PT 1/4"), Female	-
	XX : Others	on request
Liquid filling	0 : Dry	-
	1 : Glycerin	120,400
	2 : Silicon	314,300
Unit of measurement	B : bar	-
	K : kPa	-
	M : MPa	-
	P : psi	-
	D : dual scale (MPa-inner & bar-outer)	-
	X : others	on request
Pressure Ranges	R28 : 0...50 kPa	
	R29 : 0...0.1 MPa	
	R31 : 0...0.2 MPa	
	R33 : 0...0.3 MPa	
	R34 : 0...0.4 MPa	
	R36 : 0...0.6 MPa	
	R37 : 0...1 MPa	

Options

1. On dial face	OR : Other pressure range per pcs	15,100
	ND : New dial face design	120,400
	NF : New dial face printing cost per pcs	4,600
	GM : Green marking per pcs	4,600
	CD : New dial face design with company logo	75,200
2. Accessories	RS : Restrictor screw in socket hole for high pulsation	2,300
	UC : U-clamp for back connection, steel	15,100
	NO : Washing for application "USE NO OIL" per pcs, at least ≥ 10	3,800
	SG : Safety glass	3,100
	FF : Front flange with 3-hole, stainless steel	3,800
	BF : Back flange with 3-hole, stainless steel	3,800
	3W : 3-way manifold	315,800
	5W : 5-way manifold	588,000
	TP : St steel tag plate, 60 x 20 x 0.5t	9,000
3. Certificates	MC : Manufacture calibration certificate	8,500
	KC : KOLAS / ilac-MRA calibration certificate	refer to KOLAS list price