

Piezoresistive silicon differential pressure transmitter  
 St. steel body for industrial application  
 with Declaration of conformity, CE

**DAHO**

Since January, 2026



Model **EDN.350**  
 Sensor type *Piezo\_resistive silicon sensor*  
 Accuracy  $\leq 0.5\% \text{ FS} \ \& \ 0.25\% \text{ F.S} \ \& \ 0.1\% \text{ F.S}$   
 Wetted parts: *st. steel 316L*  
 Application: *air, oil, water as well as aggesive media*

**Pressure Transmitter**      **Model**      **기본 판매가격(원)**

<b>Model:</b>	<b>EDN.350</b>	A4 : accuracy $\leq 0.5\%$	677,600
		A7 : accuracy $\leq 0.25\%$	847,000
		A9 : accuracy $\leq 0.1\%$	1,129,400

**Scope**      **Code**      **Specifications**      **선택 사양 추가금액(원)**

Analog output signals	O1	: 4...20mA, 2-wire system	-
	O2	: 0...10V, 3-wire system	-
	O3	: 0...5V, 3-wire system	-
	O4	: 1...5V, 3-wire system	-
Electrical connection	D	: DIN 43650 A	-
	M	: M12 plug	21,000
	C	: 2m Cable	10,300
	H	: General head, similar to thermocouple head	43,000
Pressure connection	G4	: female G 1/4" + female G1/4"	-
	XX	: Others	additional costs
Pressure Ranges / bar	R128	: 0...40 mbar	-
	R129	: 0...60 mbar	-
	R131	: 0...100 mbar	-
	R134	: 0...200 mbar	-
	R137	: 0...400 mbar	-
	R21	: 0...600 mbar	-
	R23	: 0...1 bar	-
	R26	: 0...1.6 bar	-
	R28	: 0...2.5 bar	-
	R30	: 0...4 bar	-
	R32	: 0...6 bar	-
	R33	: 0...10 bar	-
	R35	: 0...16 bar	-
R37	: 0...25 bar	-	
R38	: 0...35 bar	-	



Piezoresistive silicon pressure transmitter  
St. steel body for industrial application  
with Declaration of conformity, CE



**A. Options**

Specifications	Descriptions	Unit price(₩)
Operating temperature	T4 : -40...+125 °C	63,200
4-wires system for current	C4 : 4...20mA, 4-wire system (+Vcc, +signal, -Vcc, -signal)	11,600
Postprocess	AC50 : Corrosion-protective covering with Teflon to wetted parts	13,900
	AC51 : O-ring PTFE, FKM80 for sealing with sensor	3,100
Accessories	AC45 : LCD Square Indicator, only for 4...20mA output	158,000
	AC46 : LED Square Indicator, only for 4...20mA output	158,000
	TP : St steel tag plate, 60 x 20 x 0.5t	10,000
	GK4 : Gasket, aluminium for thread G1/4"	3,100
Flying cable / IP67	ACM : 2m flying cable + additional extension cable /m	2,200
Certificates	DMCC : DAHO manufacturing calibration card	price included
	KC : KOLAS calibration certificate	KOLAS 교정비용 참조

**B. Specification of accessories**

Product code	Photos	Specifications
AC45		Model : Square Indicator, LCD Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43650A made of plastic
AC46		Model : Square Indicator, LED Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43650A, plastic made of plastic

**C. KOLAS 국제공인 교정성적서 수수료**

분류 번호	측정기명		교정 주기	교정료			
	압력변환기 / 전송기			표준, 종합 교정절차시 실비	기본교정료	표준소급료	VAT별도
20412	1	압력변환기-절대압용 압력계			171,500	17,150	188,650
	2	압력변환기-게이지압용 압력계			114,700	11,470	126,170
	3	압력변환기-차압용 압력계			118,200	11,820	130,020
	4	압력변환기-기압계용 압력계			114,700	11,470	126,170
	5	압력변환기-고압용 압력계 (100MPa 이상인 계기)		100 MPa 이상인 계기	143,600	14,360	157,960
	6	압력변환기-미압용 압력계 (0.01 MPa 이하인 계기)		0.01 MPa 이하인 계기	124,100	12,410	136,510
	7	압력변환기-동압용 압력계		실비			

※ 다호 제품 또는 수입공급하는 제품을 구매할 경우에 "KOLAS 국제공인 교정료"에서 50% 할인 적용하며, 연간계약 또는 특별고정할인 그리고 구매수량에 따른 할인 적용업체는 중복할인적용이 되지 않습니다.