



Model	ODi-5G
Sensor type	Piezoresistive silicon sensor
Accuracy	Accuracy 0.4% FS
Wetted part	304SS
Application	Gas or liquid

(Currency : KRW)

Specification	Code	List Price
		<i>Standard Price</i>
Model:	ODi-5G : 100 mm	241,100
		<i>[QPDR: Group "A"] Additional Prices</i>
Pressure Connection	G2 : PF 1/2"	-
	N2 : NPT 1/2"	on request
Pressure Range / bar	R23 : -1...0	
	R106 : -50...50 mbar	29,500
	R08 : -1...10 bar	
	R23 : 0...1	
	R130 : 0...60 mbar	
	R131 : 0...100 mbar	
	R135 : 0...250 mbar	
	R28 : 0...2.5	
	R30 : 0...4	
	R32 : 0...6	
	R33 : 0...10	
	R35 : 0...16	No extra costs
	R37 : 0...25	
	R39 : 0...40 / stock	
	R41 : 0...60	
	R43 : 0...100 / stock	
	R45 : 0...160	
	R47 : 0...250 / stock	
R50 : 0...400 / stock		
R53 : 0...600 / stock		
R55 : 0...1000	110,600	

Option

Accessories	AC40 : Cooling device up to 200 °C	306,200
	AC41 : Cooling device up to 300 °C	400,000
	PCA : Adapter, female G1/4" x male R1/4",R3/8",R1/2",G3/8",G1/2"	21,600
	Case : Plastic case	55,000
Certificates	DMCC : DAHO manufacturing calibration card	<i>Price included</i>
	KC : KOLAS calibration certificate	<i>Refer to KOLAS List Price</i>