



Model EDA.370
Sensor type Piezo_resistive pressure silicon sensor
Accuracy $\leq 0.5\% / 0.25\% / 0.1\%$ F.S,
Wetted parts: st. steel 316L
Application: air, oil, water as well as aggesive media

Pressure Transmitter	Model	기본 판매가격(원)	
Model: EDA.370	A4 : accuracy $\leq 0.5\%$	243,900	
	A7 : accuracy $\leq 0.25\%$	325,400	
	A9 : accuracy $\leq 0.1\%$	487,800	
Scope	Code	Specifications	선택사양 추가금액(원)
Analog output signals	O1	4...20mA, 2-wire system	under construction
	O2	0...10V, 3-wire system	
	O3	0...5V, 3-wire system	-
	O4	1...5V, 3-wire system	
Electrical connection	P	mPm plug	-
	D	DIN43650A	
Pressure connection	R4	R 1/4" (PT 1/4")	
	R3	R 3/8" (PT 3/8")	
	R2	R 1/2" (PT 1/2")	-
	G4	G 1/4" (PF 1/4")	
	G3	G 3/8" (PF 3/8")	
	G2	G 1/2" (PF 1/2")	
	XX	Others	문의 & 추가금액발생
Pressure Ranges / bar - pressure ≤ 40 bar, PR reference pressure - pressure > 60 bar, PA sealed pressure	R19	-1...0	
	R23	0...1	
	R26	0...1.6	
	R28	0...2.5	
	R30	0...4	
	R32	0...6	
	R33	0...10	
	R35	0...16	
	R37	0...25	-
	R39	0...40	
	R41	0...60	
	R43	0...100	
	R45	0...160	
	R47	0...250	
	R50	0...400	
	R53	0...600	
	R55	0...1000	

※ 위에서 언급된 압력범위 0...50 bar 까지는 reference pressure (PR) 이며,
0...50 bar를 초과하는 압력범위는 sealed pressure (PA).
절대압(PAA)은 추가금액이 발생하며, 제작공급기간은 대략 5~6주 이상.

추가선택사양

Absolute pressure	PAA	: absolute pressure range [5...6 weeks delivery]	105,300
Operating temperature	T4	: -40...+125 °C	63,200
4-wires system for current	C4	: 4...20mA, 4-wire system (+Vcc, +signal, -Vcc, -signal)	11,600
Accessories	AC20	: Washer, aluminium a/w G1/4"A & G1/2"A-EN 837	2,200
	AC25	: Restirctor screw [oripis] made in st. steel	2,000
	AC40	: Cooling device upto 200 °C	306,200
	AC41	: Cooling device upto 300 °C	400,000
	AC45	: LCD Square Indicator, only for 4...20mA output	158,000
	AC46	: LED Square Indicator, only for 4...20mA output	158,000
	TP	: St steel tag plate, 60 x 20 x 0.5t	10,000
	GK4	: Gasket, aluminium for thread G1/4"	3,100
Flying cable / IP67	ACM	: 2m flying cable + additional extension cable /m	2,200
Underwater plug / IP68	5MCW	: 5m underwater cable standard length	171,900
	ACMV	: additional extension underwater cable /m	6,500
Certificates	DMCC	: DAHO manufacturing calibration card	price included
	KC	: KOLAS calibration certificate	KOLAS 교정비용 참조

※ 발주시 최종 합산된 총금액에서 10 원 이하는 절사하세요

KOLAS 국제공인 인증성적서 교정료

분류 번호	측정기명		교정 주기	교정료			
20412	압력변환기 / 전송기		12	표준, 종합 교정절차시 실비	기본교정료	표준소급료	VAT별도
	1	압력변환기-절대압용 압력계			178,300	17,830	196,130
	2	압력변환기-게이지압용 압력계			119,200	11,920	131,120
	3	압력변환기-차압용 압력계			122,900	12,290	135,190
	4	압력변환기-기압계용 압력계			119,200	11,920	131,120
	5	압력변환기-고압용 압력계 (100MPa 이상인 계기)		100 MPa 이상인 계기	149,300	14,930	164,230
	6	압력변환기-미압용 압력계 (0.01 MPa 이하인 계기)		0.01 MPa 이하인 계기	129,000	12,900	141,900
	7	압력변환기-동압용 압력계		실비			

■ 다호가 자체제작하는 제품 또는 직접수입공급하는 제품을 구매하는 경우에
"KOLAS 국제공인 교정료"에서 50% 할인 적용하며,
다호와 연간 할인 계약 또는 특별고정할인 그리고 구매수량에 따른 할인 적용업체는
중복할인 적용이 되지 않습니다.

Product code	Photos	Specifications
AC20		Model : Washer, aluminium for pressure connection EN837 Applied for : Sealing for G1/4" & G1/2" Thickness : 4 mm Outer diameter : 14.5 mm
AC25		Product name: : Restrictor screw [oripis] Material : stainless steel Application: : against pulsation Hole diameter : 0.15mm Outer : less 3mm
AC40		Model : Cooling device upto 200 °C Application : cooling down temperature 200 °C only for pressure transmitters Material : SUS 316 No. of fins : 5 Pressure conn. : G1/4", G1/2"
AC41		Model : Cooling device Application : Temperature upto 300°C a/w diaphragm seals Material : SUS 316 No. of fins : 5 Pressure conn. : G1/4", G1/2"
AC45		Model : Square Indicator, LCD Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43650A made of plastic
AC46		Model : Square Indicator, LED Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43650A, plastic made of plastic