



Model	EDL.335
Sensor type	Piezo_resistive silicon sensor
Accuracy	$\leq 0.5\%$, $\leq 0.25\%$, $\leq 0.1\%$ F.S
Wetted parts:	all st. steel
Application:	Scrubber

Pressure Transmitter	Model	Basic price(원)
Model: EDL.335	A4 : accuracy $\leq 0.5\%$	206,300
	A7 : accuracy $\leq 0.25\%$	245,000

Scope	Code	Specifications	Additional costs(원)
Analog output signals	O1	4...20mA, 2-wire system	-
	O2	0...10V, 3-wire system	-
	O3	0...5V, 3-wire system	-
	O4	1...5V, 3-wire system	-
Electrical connection	D	DIN 43650 A	-
	M	M12 plug	21,000
	C	2m Cable	10,300
Pressure connection	G4	G1/4"(PF1/4") with 6 mm hole	-
	R4	R1/4"(PT1/4") with 6 mm hole	-
	G2	G1/2"(PF1/2") with 12.4 mm hole	-
	XX	Others	on request
Pressure Ranges / mbar	R124	- 25 mbar...+ 25 mbar	-
	R127	- 50 mbar...+ 50 mbar	
	R132	- 250 mbar...+ 250 mbar	
	R135	- 500 mbar...+ 500 mbar	

추가공통 선택사항 [Options]

Absolute pressure	PAA : absolute pressure range [5...6 weeks delivery]	105,300
Operating temperature	T4 : -40...+125 °C	63,200
4-wires system for current	C4 : 4...20mA, 4-wire system (+Vcc, +signal, -Vcc, -signal)	11,600
Postprocess	AC50 : Corrosion-protective covering with Teflon to wetted parts	14,000
	AC51 : O-ring ETFE, FKM80 for sealing with sensor	3,300
Accessories	AC20 : Washer, aluminium a/w G1/4"A & G1/2"A-EN 837	2,200
	AC23 : Metal gasket(Sealing gasket), 316L for hole 12.4mm	6,000
	AC24 : Metal gasket(Sealing gasket), brass for hole 12.4mm	4,200
	AC25 : Restirctor screw [oripis] made of st. steel	2,000
	AC40 : Cooling device upto 200 °C	306,200
	AC41 : Cooling device upto 300 °C	400,000
	TP : St steel tag plate, 60 x 20 x 0.5t	10,000
	GK4 : Gasket, aluminium for thread G1/4"	3,100
Flying cable / IP67	ACM : 2m flying cable + additional extension cable /m	2,200
Certificates	DMCC : DAHO manufacturing calibration card	price included
	KC : KOLAS calibration certificate	KOLAS 교정비용 참조

KOLAS 국제인증 교정수수료

	압력변환기 / 전송기	12	표준, 종합 교정절차시 실비	기본교정료	표준소급료	VAT별도
20412	1 압력변환기-절대압용 압력계			178,300	17,830	196,130
	2 압력변환기-게이지압용 압력계			119,200	11,920	131,120
	3 압력변환기-차압용 압력계			122,900	12,290	135,190
	4 압력변환기-기압계용 압력계			119,200	11,920	131,120
	5 압력변환기-고압용 압력계 (100MPa 이상인 계기)		100 MPa 이상인 계기	149,300	14,930	164,230
	6 압력변환기-미압용 압력계 (0.01 MPa 이하인 계기)		0.01 MPa 이하인 계기	129,000	12,900	141,900
	7 압력변환기-동압용 압력계		실비			

※ 다호 제품 또는 수입공급하는 제품을 구매할 경우에 "KOLAS 국제공인 교정료"에서 50% 할인 적용하며,
연간계약 또는 특별고정할인 그리고 구매수량에 따른 할인 적용업체는 중복할인이 되지 않습니다.

Product code	Photos	Specifications	
AC20		Model	: Washer, aluminium for pressure connection EN837
		Applied for	: Sealing for G1/4" & G1/2"
		Thickness	: 4 mm
		Outer diameter	: 14.5 mm
AC23		Product name:	: Metal gasket for hole 12.4mm
		Material	: st. steel 316L
		Application:	: Sealing washer for high temperature
		Hole diameter	:
		Outer	:
AC24		Product name:	: Metal gasket for hole 12.4mm
		Material	: Brass
		Application:	: Sealing washer for high temperature
		Hole diameter	:
		Outer	:
AC25		Product name:	: Restrictor screw [oripis]
		Material	: stainless steel
		Application:	: against pulsation
		Hole diameter	: 0.15mm
		Outer	: less 3mm
AC40		Model	: Cooling device upto 200 °C
		Application	: cooling down temperature 200 °C only for pressure transmitters
		Material	: SUS 316
		No. of fins	: 5
		Pressure conn.	: G1/4", G1/2"
AC41		Model	: Cooling device
		Application	: Temperature upto 300 °C a/w diaphragm seals
		Material	: SUS 316
		No. of fins	: 5
		Pressure conn.	: G1/4", G1/2"
AC45		Model	: Square Indicator, LCD
		Application	: 4..20mA output only
		Display	: -1999...9999
		Sampling rate	: 3 times / sec
		Electrical conn.	: a/w DIN 43650A made of plastic
AC46		Model	: Square Indicator, LED
		Application	: 4..20mA output only
		Display	: -1999...9999
		Sampling rate	: 3 times / sec
		Electrical conn.	: a/w DIN 43650A, plastic made of plastic