



Model EDA.371
Sensor type Piezo_resistive pressure silicon sensor
Accuracy $\leq 0.5\% / 0.25\% / 0.1\% \text{ F.S.}$
Wetted parts: st. steel 316L
Application: air, oil, water as well as aggesive media

Pressure Transmitter	Model	기본 판매가격(원)	
Model: EDA.370	A4 : accuracy $\leq 0.5\%$	269,400	
	A7 : accuracy $\leq 0.25\%$	359,200	
	A9 : accuracy $\leq 0.1\%$	538,800	
Scope	Code	Specifications	선택사양 추가금액(원)
Analog output signals	O1	4...20mA, 2-wire system	
	O2	0...10V, 3-wire system	
	O3	0...5V, 3-wire system	
	O4	1...5V, 3-wire system	
Electrical connection	P	mPm plug	
	D	DIN43650A	
Pressure connection	R4	R 1/4" (PT 1/4")	
	R3	R 3/8" (PT 3/8")	
	R2	R 1/2" (PT 1/2")	
	G4	G 1/4" (PF 1/4")	
	G3	G 3/8" (PF 3/8")	
	G2	G 1/2" (PF 1/2")	
	XX	Others	문의 & 추가금액발생
Pressure Ranges / bar - pressure $\leq 40 \text{ bar}$, PR reference pressure - pressure $> 60 \text{ bar}$, PA sealed pressure	R19	-1...0	
	R23	0...1	
	R26	0...1.6	
	R28	0...2.5	
	R30	0...4	
	R32	0...6	
	R33	0...10	
	R35	0...16	
	R37	0...25	
	R39	0...40	
	R41	0...60	
	R43	0...100	
	R45	0...160	
	R47	0...250	
	R50	0...400	
	R53	0...600	
	R55	0...1000	

※ 위에서 언급된 압력범위 0...50 bar 까지는 reference pressure (PR) 이며,
0...50 bar를 초과하는 압력범위는 sealed pressure (PA).
절대압(PAA)은 추가금액이 발생하며, 제작공급기간은 대략 5~6주 이상.

추가선택사양

Absolute pressure	PAA	: absolute pressure range [5...6 weeks delivery]	105,300
Operating temperature	T4	: -40...+125 °C	63,200
4-wires system for current	C4	: 4...20mA, 4-wire system (+Vcc, +signal, -Vcc, -signal)	11,600
Accessories	AC20	: Washer, aluminium a/w G1/4"A & G1/2"A-EN 837	2,200
	AC25	: Restirctor screw [oripis] made in st. steel	2,000
	AC40	: Cooling device upto 200 °C	306,200
	AC41	: Cooling device upto 300 °C	400,000
	AC45	: LCD Square Indicator, only for 4...20mA output	158,000
	AC46	: LED Square Indicator, only for 4...20mA output	158,000
	TP	: St steel tag plate, 60 x 20 x 0.5t	10,000
	GK4	: Gasket, aluminium for thread G1/4"	3,100
Flying cable / IP67	ACM	: 2m flying cable + additional extension cable /m	2,200
Underwater plug / IP68	5MCW	: 5m underwater cable standard length	171,900
	ACMV	: additional extension underwater cable /m	6,500
Certificates	DMCC	: DAHO manufacturing calibration card	price included
	KC	: KOLAS calibration certificate	KOLAS 교정비용 참조

※ 발주시 최종 합산된 총금액에서 10 원 이하는 절사

KOLAS 국제공인 인증성적서 교정료

분류 번호	측정기명		교정 주기	교정료			
20412	압력변환기 / 전송기		12	표준, 종합 교정절차시 실비	기본교정료	표준소급료	VAT별도
	1	압력변환기-절대압용 압력계			178,300	17,830	196,130
	2	압력변환기-게이지압용 압력계			119,200	11,920	131,120
	3	압력변환기-차압용 압력계			122,900	12,290	135,190
	4	압력변환기-기압계용 압력계			119,200	11,920	131,120
	5	압력변환기-고압용 압력계 (100MPa 이상인 계기)		100 MPa 이상인 계기	149,300	14,930	164,230
	6	압력변환기-미압용 압력계 (0.01 MPa 이하인 계기)		0.01 MPa 이하인 계기	129,000	12,900	141,900
	7	압력변환기-동압용 압력계		실비			

■ 다호가 자체제작하는 제품 또는 직접수입공급하는 제품을 구매하는 경우에
"KOLAS 국제공인 교정료" 에서 50% 할인 적용하며,
다호와 연간 할인 계약 또는 특별고정할인 그리고 구매수량에 따른 할인 적용업체는
중복할인적용이 되지 않습니다.

Product code	Photos	Specifications
AC20		Model : Washer, aluminium for pressure connection EN837 Applied for : Sealing for G1/4" & G1/2" Thickness : 4 mm Outer diameter : 14.5 mm
AC25		Product name: : Restrictor screw [oripis] Material : stainless steel Application: : against pulsation Hole diameter : 0.15mm Outer : less 3mm
AC40		Model : Cooling device upto 200 °C Application : cooling down temperature 200 °C only for pressure transmitters Material : SUS 316 No. of fins : 5 Pressure conn. : G1/4", G1/2"
AC41		Model : Cooling device Application : Temperature upto 300°C a/w diaphragm seals Material : SUS 316 No. of fins : 5 Pressure conn. : G1/4", G1/2"
AC45		Model : Square Indicator, LCD Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43650A made of plastic
AC46		Model : Square Indicator, LED Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43650A, plastic made of plastic